Számítógépes számelmélet

Járai Antal

Ezek a programok csak szemléltetésre szolgálnak

▶ 1. A prímek eloszlása, szitálás

▶ 2. Egyszerű faktorizálási módszerek

▶ 3. Egyszerű prímtesztelési módszerek

▼ 4. Lucas-sorozatok

```
> restart; with(numtheory);
```

[*GIgcd*, *bigomega*, *cfrac*, *cfracpol*, *cyclotomic*, *divisors*, *factorEQ*, *factorset*, *fermat*, *imagunit*, *index*, *integral_basis*, *invcfrac*, *invphi*, *issqrfree*, *jacobi*, *kronecker*, λ, *legendre*, *mcombine*, *mersenne*, *migcdex*, *minkowski*, *mipolys*, *mlog*, *mobius*, *mroot*, *msqrt*, *nearestp*, *nthconver*, *nthdenom*, *nthnumer*, *nthpow*, *order*, *pdexpand*, ϕ, π, *pprimroot*, *primroot*, *quadres*, *rootsunity*, *safeprime*, σ, *sq2factor*, *sum2sqr*, τ, *thue*] (4.1)

▼ 4.1. Definíció.

```
> a:=-3; b:=2; for n to 10 do [(a^n-b^n)/(a-b),a^n+b^n]; od;
```

$$a := -3$$

$$b := 2$$

$$[1, -1]$$

$$[-1, 13]$$

$$[7, -19]$$

$$[-13, 97]$$

$$[55, -211]$$

$$[-133, 793]$$

$$[463, -2059]$$

$$[-1261, 6817]$$
$$[4039, -19171]$$
$$[-11605, 60073] \tag{4.1.1}$$

▶ 4.2. Megjegyzés.

▼ 4.3. Példa.

```
> a:=(1+sqrt(5))/2; b:=(1-sqrt(5))/2; for n to 10 do [expand(
  (a^n-b^n)/(a-b)),expand(a^n+b^n)]; od;
```

$$a := \frac{1}{2} + \frac{1}{2}\sqrt{5}$$
$$b := \frac{1}{2} - \frac{1}{2}\sqrt{5}$$
$$[1, 1]$$
$$[1, 3]$$
$$[2, 4]$$
$$[3, 7]$$
$$[5, 11]$$
$$[8, 18]$$
$$[13, 29]$$
$$[21, 47]$$
$$[34, 76]$$
$$[55, 123] \tag{4.3.1}$$

▼ 4.4. Rekurzió számoláshoz.

```
> #
  # This procedure calculate the Lucas sequence terms
  # [U[n],V[n],U[n+1],V[n+1]]. If the parameter N also given
  # then the calculations are done mod N. Here U[n]=a^n-b^n)/(a
  -b)
  # and V[n]=a^n+b^n, where a,b are the roots of x^2-Px+Q=0.
  #

  lucasUV:=proc(n,P,Q,N) local L,B,i,Qk;
  B:=convert(n,base,2);
  Qk:=1;
  if nargs=3 then
```

```
    L:=[0,2,1,P];
    for i from nops(B) to 1 by -1 do
      if B[i]=0 then
        L:=[L[1]*L[2],L[2]^2-2*Qk,L[3]*L[2]-Qk,L[4]*L[2]-P*Qk];
        Qk:=Qk^2;
      else
        L:=[L[3]*L[2]-Qk,L[4]*L[2]-P*Qk,L[3]*L[4],L[4]^2-2*Q*
  Qk];
        Qk:=Qk^2*Q;
      fi;
    od;
  else
    L:=[0,2 mod N,1,P mod N];
    for i from nops(B) to 1 by -1 do
      if B[i]=0 then
        L:=[L[1]*L[2] mod N,L[2]&^2-2*Qk mod N,\
        L[3]*L[2]-Qk mod N,L[4]*L[2]-P*Qk mod N];
        Qk:=Qk&^2 mod N;
      else
        L:=[L[3]*L[2]-Qk mod N,L[4]*L[2]-P*Qk mod N,\
        L[3]*L[4] mod N,L[4]&^2-2*Q*Qk mod N];
        Qk:=Qk&^2*Q mod N;
      fi;
    od;
  fi; L end;
```

$$lucasUV := \mathbf{proc}(n, P, Q, N) \tag{4.4.1}$$

local L, B, i, Qk;

$B := convert(n, base, 2)$;

$Qk := 1$;

if $nargs = 3$ **then**

$L := [0, 2, 1, P]$;

for i **from** $nops(B)$ **by** -1 **to** 1 **do**

if $B[i] = 0$ **then**

$L := [L[1] * L[2],$

$L[2]\text{^}2 - 2 * Qk, L[3] * L[2] - Qk, L[4] * L[2] - P * Qk]$;

$Qk := Qk\text{^}2$

else

$L := [L[3] * L[2] - Qk, L[4] * L[2] - P * Qk,$

$L[3] * L[4], L[4]\text{^}2 - 2 * Q * Qk]$;

$Qk := Qk\text{^}2 * Q$

end if

```
        end do
    else
        L := [0, mod(2, N), 1, mod(P, N)];
        for i from nops(B) by -1 to 1 do
            if B[i] = 0 then
                L := [mod(L[1]*L[2], N), mod(L[2] &^ 2 - 2*Qk, N),
                mod(L[3]*L[2] - Qk, N), mod(L[4]*L[2] - P*Qk, N)];
                Qk := mod(Qk &^ 2, N)
            else
                L := [mod(L[3]*L[2] - Qk,
                N), mod(L[4]*L[2] - P*Qk, N), mod(L[3]*L[4], N),
                mod(L[4] &^ 2 - 2*Q*Qk, N)];
                Qk := mod(Qk &^ 2*Q, N)
            end if
        end do
    end if;
    L
end proc
```

```
> #
  # This procedure calculate the Lucas sequence terms
  # [V[n],V[n+1]]. If the parameter N also given
  # then the calculations are done mod N. Here V[n]=a^n+b^n,
  # where a,b are the roots of x^2-Px+Q=0.
  #

  lucasV:=proc(n,P,Q,N) local L,B,i,Qk;
  B:=convert(n,base,2);
  Qk:=1;
  if nargs=3 then L:=[2,P];
    for i from nops(B) to 1 by -1 do
      if B[i]=0 then
        L:=[L[1]^2-2*Qk,L[2]*L[1]-P*Qk]; Qk:=Qk^2;
      else
        L:=[L[2]*L[1]-P*Qk,L[2]^2-2*Q*Qk]; Qk:=Qk^2*Q;
      fi;
    od;
  else L:=[2 mod N,P mod N];
    for i from nops(B) to 1 by -1 do
      if B[i]=0 then
```

```
      L:=[L[1]&^2-2*Qk mod N,L[2]*L[1]-P*Qk mod N]; Qk:=Qk&^2
  mod N;
    else
      L:=[L[2]*L[1]-P*Qk mod N,L[2]&^2-2*Q*Qk mod N]; Qk:=
  Qk&^2*Q mod N;
    fi;
  od;
  fi; L end;
```

$$lucasV := \mathbf{proc}(n, P, Q, N) \tag{4.4.2}$$

$\mathbf{local}\ L, B, i, Qk;$

$B := convert(n, base, 2);$

$Qk := 1;$

$\mathbf{if}\ nargs = 3\ \mathbf{then}$

$L := [2, P];$

$\mathbf{for}\ i\ \mathbf{from}\ nops(B)\ \mathbf{by}\ -1\ \mathbf{to}\ 1\ \mathbf{do}$

$\mathbf{if}\ B[i] = 0\ \mathbf{then}$

$L := [L[1]\text{^}2 - 2 * Qk, L[1] * L[2] - P * Qk];$

$Qk := Qk\text{^}2$

$\mathbf{else}$

$L := [L[1] * L[2] - P * Qk,$

$L[2]\text{^}2 - 2 * Q * Qk];$

$Qk := Qk\text{^}2 * Q$

$\mathbf{end\ if}$

$\mathbf{end\ do}$

$\mathbf{else}$

$L := [mod(2, N), mod(P, N)];$

$\mathbf{for}\ i\ \mathbf{from}\ nops(B)\ \mathbf{by}\ -1\ \mathbf{to}\ 1\ \mathbf{do}$

$\mathbf{if}\ B[i] = 0\ \mathbf{then}$

$L := [mod(L[1]\ \&\text{^}\ 2 - 2 * Qk, N),$

$mod(L[1] * L[2] - P * Qk, N)];$

$Qk := mod(Qk\ \&\text{^}\ 2, N)$

$\mathbf{else}$

$L := [mod(L[1] * L[2] - P * Qk, N), mod(L[2]\ \&\text{^}\ 2 - 2 * Q *$

$Qk,$

$N)];$

```
            Qk := mod(Qk &^ 2 * Q, N)
        end if
    end do
end if;
L
end proc
```

▶ 4.5. Feladat.

▶ 4.6. Megjegyzés.

▶ 4.7. Definíció.

▶ 4.8. Tétel.

▼ 4.9. Feladat.

```
> #
  # This procedure do primality test for the odd number n
  # using the set S of all factors of n+1 and the Lucas
  # sequence corresponding to the roots of x^2-Px+1.
  #

  naiveplustest:=proc(n::posint,S::list(posint),P::integer)
  local D,q,L;
  D:=P^2-4; modp(D,4); if %=2 or %=3 then RETURN(FAIL) fi;
  igcd(2*D,n);
  if %<>1 then
    if %<n then RETURN(false) else RETURN(FAIL) fi;
  fi;
  if jacobi(D,n)<>-1 then RETURN(FAIL) fi;
  L:=lucasUV(n+1,P,1,n);
  if L[1]<>0 or L[2]<>2 then RETURN(false) fi;
  for q in S do
    L:=lucasUV((n+1)/q,P,1,n);
    if L[1]=0 and L[2]=2 then RETURN(FAIL) fi;
  od; true end;
```

```
naiveplustest := proc(n::posint, S::(list(posint)), P::integer)
    local D, q, L;
    D := P^2 - 4;
    modp(D, 4);
```

(4.9.1)

```
    if `%` = 2 or `%` = 3 then
        RETURN(FAIL)
    end if;
    igcd(2*D, n);
    if `%` <> 1 then
        if `%` < n then
            RETURN(false)
        else
            RETURN(FAIL)
        end if
    end if;
    if numtheory:-jacobi(D, n) <> -1 then
        RETURN(FAIL)
    end if;
    L := lucasUV(n+1, P, 1, n);
    if L[1] <> 0 or L[2] <> 2 then
        RETURN(false)
    end if;
    for q in S do
        L := lucasUV((n+1)/q, P, 1, n);
        if L[1] = 0 and L[2] = 2 then
            RETURN(FAIL)
        end if
    end do;
    true
end proc
```

```
> naiveplustest(7,[2],3);
```

$$true \tag{4.9.2}$$

```
> #
  # This procedure do primality test for the odd number n
  # using the set S of all factors of n+1.  Try all Lucas
  # sequences  with Q=1 and P in interval II.
  #

  naiveplustests:=proc(n::posint,S::list(posint),II::range
```

```
   (integer))
   local r,P;
   for P from op(1,II) to op(2,II) do
     r:=naiveplustest(n,S,P);
     if r<>FAIL then RETURN(r) fi;
   od; FAIL end;
```

$$naiveplustests := \mathbf{proc}(n::posint, S::(list(posint)), II::(range(integer))) \tag{4.9.3}$$

local r, P,

for P **from** $op(1, II)$ **to** $op(2, II)$ **do**

$r := naiveplustest(n, S, P)$;

if $r <> FAIL$ **then**

$RETURN(r)$

end if

end do;

$FAIL$

end proc

```
> naiveplustests(7,[2],1..2); naiveplustests(7,[2],1..3);
```

$$FAIL$$

$$true \tag{4.9.4}$$

▶ 4.10. Lucas-típusú teszt.

▼ 4.11. Feladat.

```
> #
  # This procedure do primality test for the odd number n
  # using a large enough set S of factors of n+1 and the Lucas
  # sequence corresponding to the roots of x^2-Px+1.
  #

  plustest:=proc(n::posint,S::list(posint),P::integer)
  local D,q,L; if n=1 then RETURN(false) fi;
  D:=P^2-4; modp(D,4); if %=2 or %=3 then RETURN(FAIL) fi;
  igcd(2*D,n);
  if %<>1 then
    if %<n then RETURN(false) else RETURN(FAIL) fi;
  fi;
  if jacobi(D,n)<>-1 then RETURN(FAIL) fi;
  L:=lucasUV(n+1,P,1,n);
  if L[1]<>0 or L[2]<>2 then RETURN(false) fi;
  for q in S do
```

```
    L:=lucasUV((n+1)/q,P,1,n);
    igcd(L[2]-2,L[1],n);
    if %<>1 then
      if %<n then RETURN(false) else RETURN(FAIL) fi;
    fi;
  od; true end;
```

```
plustest := proc(n::posint, S::(list(posint)), P::integer)                    (4.11.1)
    local D, q, L;
    if n = 1 then
        RETURN(false)
    end if;
    D := P^2 - 4;
    modp(D, 4);
    if `%` = 2 or `%` = 3 then
        RETURN(FAIL)
    end if;
    igcd(2*D, n);
    if `%` <> 1 then
        if `%` < n then
            RETURN(false)
        else
            RETURN(FAIL)
        end if
    end if;
    if numtheory:-jacobi(D,
    n) <> -1 then
        RETURN(FAIL)
    end if;
    L := lucasUV(n + 1, P, 1, n);
    if L[1] <> 0 or L[2] <> 2 then
        RETURN(false)
    end if;
    for q in S do
        L := lucasUV((n + 1) / q, P, 1, n);
```

```
        igcd(L[2] - 2, L[1], n);
        if `%` <> 1 then
            if `%` < n then
                RETURN(false)
            else
                RETURN(FAIL)
            end if
        end if
    end do;
    true
end proc
```

```
> plustest(7,[2],3);
```

$$true \tag{4.11.2}$$

```
> #
  # This procedure do primality test for the odd number n
  # using a large enough set S of factors of n+1. Try all Lucas
  # sequences with Q=1 and P in interval II.
  #

  plustests:=proc(n::posint,S::list(posint),II::range(integer))
  local r,P;
  for P from op(1,II) to op(2,II) do
    r:=plustest(n,S,P);
    if r<>FAIL then RETURN(r) fi;
  od; FAIL end;
```

$$plustests := \mathbf{proc}(n::posint,\ S::(list(posint)),\ II::(range(integer))) \tag{4.11.3}$$

```
    local r,
    P;
    for P from op(1, II) to op(2, II) do
        r := plustest(n, S, P);
        if r <> FAIL then
            RETURN(r)
        end if
    end do;
    FAIL
end proc
```

```
> plustests(7,[2],1..2); plustests(7,[2],1..3);
```

FAIL

true (4.11.4)

4.12. Feladat.

```
> #
  # This procedure do primality test for the number h*2^n-1
  # with n>1 and odd h<2^n using the Lucas sequence
  corresponding
  # to the roots of x^2-Px+1.
  #

  specplustest:=proc(h::posint,n::posint,P::integer) local D,L,
  N;
  if h>=2^n then error "first parameter is too large",h fi;
  if type(h,even) then error "first parameter have to be odd",h
  fi;
  if n<2 then error "second parameter is too small",h fi;
  N:=h*2^n-1;
  D:=P^2-4; modp(D,4); if %=2 or %=3 then RETURN(FAIL) fi;
  igcd(2*D,N);
  if %<>1 then
    if %<n then RETURN(false) else RETURN(FAIL) fi;
  fi;
  if jacobi(D,N)<>-1 then RETURN(FAIL) fi;
  L:=lucasUV(N+1,P,1,N);
  if L[1]<>0 or L[2]<>2 then RETURN(false) fi;
  L:=lucasUV((N+1)/2,P,1,N);
  if L[1]<>0 then RETURN(false) fi;
  if L[2]<>N-2 then
      if L[2]=2 then RETURN(FAIL) else RETURN(false) fi;
  fi; true end;
```

specplustest := **proc**(*h*::*posint*, *n*::*posint*, *P*::*integer*) (4.12.1)

local D, *L*, *N*;

if 2^*n* <= *h* **then**

error "first parameter is too large", *h*

end if;

if *type*(*h*, *even*) **then**

error "first parameter have to be odd", *h*

end if;

if *n* < 2 **then**

```
        error "second parameter is too small", h
    end if;
    N := h*2^n - 1;
    D := P^2 - 4;
    modp(D, 4);
    if `%` = 2 or `%` = 3 then
        RETURN(FAIL)
    end if;
    igcd(2*D, N);
    if `%` <> 1 then
        if `%` < n then
            RETURN(false)
        else
            RETURN(FAIL)
        end if
    end if;
    if numtheory:-jacobi(D,
    N) <> -1 then
        RETURN(FAIL)
    end if;
    L := lucasUV(N+1, P, 1, N);
    if L[1] <> 0 or L[2] <> 2 then
        RETURN(false)
    end if;
    L := lucasUV(1 / 2*N+1 / 2, P, 1, N);
    if L[1] <> 0 then
        RETURN(false)
    end if;
    if L[2] <> N - 2 then
        if L[2] = 2 then
            RETURN(FAIL)
        else
```

```
            RETURN(false)
        end if
    end if;
    true
end proc
```

```
> specplustest(1,3,3);
```

$$true \tag{4.12.2}$$

```
> #
  # This procedure do primality test for the number h*2^n-1
  # with n>1 and odd h<2^n. Try all Lucas sequences  with Q=1
  # and P in interval II.
  #

  specplustests:=proc(h::posint,n::posint,II::range(integer))
  local r,P;
  if h>=2^n then error "first parameter is too large",h fi;
  if type(h,even) then error "first parameter have to be odd",h
  fi;
  if n<2 then error "second parameter is too small",h fi;
  for P from op(1,II) to op(2,II) do
    r:=specplustest(h,n,P);
    if r<>FAIL then RETURN(r) fi;
  od; FAIL end;
```

$$specplustests := \mathbf{proc}(h::posint, n::posint, II::(range(integer))) \tag{4.12.3}$$

```
    local r, P,
    if 2^n <= h then
        error "first parameter is too large", h
    end if;
    if type(h, even) then
        error "first parameter have to be odd", h
    end if;
    if n < 2 then
        error "second parameter is too small", h
    end if;
    for P from op(1, II) to op(2, II) do
        r := specplustest(h, n,
        P);
        if r <> FAIL then
```

```
            RETURN(r)
        end if
    end do;
    FAIL
end proc
```

```
> specplustests(1,3,1..2); specplustests(1,3,1..3);
```

$$FAIL$$

$$true \tag{4.12.4}$$

▶ 4.13. Számtestek.

▶ 4.14. Tétel.

▶ 4.15. Riesel-teszt.

▶ 4.16. Következmény.

▼ 4.17. Feladat.

```
> #
  # This procedure calculate a^h+a^(-h) for a unit a=r+s*sqrt
  (D)
  # with norm 1. Here r,s rational numbers, D must be a square
  # free integer. All computations are done mod N.
  #

  rieselsetup:=proc(r,s,D,h,N) local P,a;
  a:=r+s*sqrt(D);
  P:=r+s*sqrt(D)+(r-s*sqrt(D))/(r^2-s^2*D);
  if not type(P,integer) then ERROR(a+1/a, `not an integer`)
  fi;
  lucasV(h,P,1,N)[1]; end;
```

$$rieselsetup := \mathbf{proc}(r, s, \mathrm{D}, h, N) \tag{4.17.1}$$

```
    local P, a;
    a := r + s*sqrt(D);
    P := r + s*sqrt(D) + (r - s*sqrt(D)) / (r^2 - s^2*D);
    if not type(P, integer) then
        ERROR(a + 1 / a, `not an integer`)
    end if;
```

```
    lucasV(h, P, 1, N)[1]
end proc
```

4.18. Feladat.

```
> #
  # A procedure above for primality testing of h*2^n-1
  # with n>1 and odd h<2^n for which h not divisible by 3.
  #

  rieselsqrt3:=proc(h::posint,n::posint) local i,v,N;
  if h>=2^n then error "first parameter is too large",h fi;
  if type(h,even) then error "first parameter have to be odd",h
  fi;
  if modp(h,3)=0 then error "first parameter is a multiple of
  3",h fi;
  if n<2 then error "second parameter is too small",h fi;
  N:=h*2^n-1; if modp(N,3)=0 then return false fi;
  v:=rieselsetup(2,1,3,h,N);
  for i to n-2 do v:=v^2-2 mod N od;
  evalb(v=0); end;
```

```
rieselsqrt3 := proc(h::posint, n::posint)                    (4.18.1)
    local i, v, N;
    if 2^n <= h then
        error "first parameter is too large", h
    end if;
    if type(h, even) then
        error "first parameter have to be odd", h
    end if;
    if modp(h,
    3) = 0 then
        error "first parameter is a multiple of 3", h
    end if;
    if n < 2 then
        error "second parameter is too small", h
    end if;
    N := h*2^n - 1;
    if modp(N, 3) = 0 then
```

```
        return false
    end if;
    v := rieselsetup(2, 1, 3, h, N);
    for i to n - 2 do
        v := mod(v^2 - 2, N)
    end do;
    evalb(v = 0)
end proc
```

```
> #
  # Some tests.
  #

  test:=proc() local h,n;
  for h in {1,5,7} do
    for n from 4 to 20 do
      print(isprime(h*2^n-1),rieselsqrt3(h,n))
    od
  od end;
```

```
test := proc()                                                    (4.18.2)
    local h, n;
    for h in {1, 5, 7} do
        for n from 4 to 20 do
            print(isprime(h*2^n - 1), rieselsqrt3(h, n))
        end do
    end do
end proc
```

```
> test();
```

```
false, false
 true, true
false, false
 true, true
false, false
false, false
false, false
false, false
false, false
```

true, *true*
false, *false*
false, *false*
false, *false*
true, *true*
false, *false*
true, *true*
false, *false*
true, *true*
false, *false*
false, *false*
false, *false*
true, *true*
false, *false*
true, *true*
false, *false*
true, *true*
false, *false*
true, *true*
false, *false*
false, *false*
false, *false*
true, *true*
false, *false*
false, *false*
false, *false*
true, *true*
false, *false*
false, *false*
false, *false*
true, *true*
false, *false*

false, *false*

false, *false*

false, *false*

false, *false*

false, *false*

false, *false*

true, *true*

false, *false*

false, *false*

false, *false* (4.18.3)

4.19. Feladat.

```
> #
  # This procedure use iteration v<-v^2-2 starting with v=a^h+
  a^-h
  # where the quadratic unit a=r+s*sqrt(D) is given for the
  # primality testing of h*2^n-1. Here n>1 and h<2^n is odd.
  #

  riesel:=proc(h,n,r,s,D) local N,v,i;
  if h>=2^n then error "first parameter is too large",h fi;
  if type(h,even) then error "first parameter have to be odd",h
  fi;
  if n<2 then error "second parameter is too small",h fi;
  N:=h*2^n-1;
  v:=rieselsetup(r,s,D,h,N);
  for i to n-2 do v:=v^2-2 mod N od;
  evalb(v=0); end;
```

riesel := **proc**(*h*, *n*, *r*, *s*, D) (4.19.1)

local *N*, *v*, *i*;

if 2 ^ *n* <= *h* **then**

error "first parameter is too large", *h*

end if;

if *type*(*h*, *even*) **then**

error "first parameter have to be odd", *h*

end if;

if *n* < 2 **then**

```
        error "second parameter is too small", h
    end if;
    N := h*2^n - 1;
    v := rieselsetup(r, s, D, h, N);
    for i to n - 2 do
        v := mod(v^2 - 2, N)
    end do;
    evalb(v = 0)
end proc
```

```
> #
  # Some tests.
  #

  test:=proc() local h,n;
  for h in {1,5,7} do
    for n from 4 to 20 do
      print(isprime(h*2^n-1),riesel(h,n,2,1,3))
    od
  od end;
```

```
test := proc()                                                    (4.19.2)
    local h, n;
    for h in {1, 5, 7} do
        for n from 4 to 20 do
            print(isprime(h*2^n - 1), riesel(h, n, 2, 1, 3))
        end do
    end do
end proc
```

```
> test();
```

```
false, false
 true, true
false, false
 true, true
false, false
false, false
false, false
false, false
```

false, *false*

true, *true*

false, *false*

false, *false*

false, *false*

true, *true*

false, *false*

true, *true*

false, *false*

true, *true*

false, *false*

false, *false*

false, *false*

true, *true*

false, *false*

true, *true*

false, *false*

true, *true*

false, *false*

false, *false*

false, *false*

true, *true*

false, *false*

false, *false*

false, *false*

true, *true*

false, *false*

false, *false*

false, *false*

true, *true*

false, *false*

false, *false*

false, *false*

false, *false*

false, *false*

false, *false*

false, *false*

true, *true*

false, *false*

false, *false*

false, *false* (4.19.3)

4.20. Feladat.

```
> #
  # This procedure find units having the form (k+l*sqrt(D))^2/r
  # with small integers k,l and r=k^2-l^2*D in the
  # quadratic extension of the rationals with sqrt(D).
  # D must be a square free integer. The numbers with |k|,|l|<=
  B
  # are tested. We remark that taking -r instead of r we get an
  # other unit. The list of all [k,l,r] is given back.
  #

  findunit:=proc(D,B) local k,l,r,a,b,n,L;
  L:=[];
  for k from 0 to B do
    for l from -B to B do
      r:=k^2-l^2*D;
      if r<>0 then
        a:=(k^2+l^2*D)/r; b:=2*k*l/r;
        if D mod 4=1 then n:=a^2-a*b-b^2*(D-1)/4
        else n:=a^2-D*b^2 fi;
        if n=1 and igcd(k,l,r)=1 then L:=[op(L),[k,l,r]] fi
      fi
    od
  od; L end;
```

findunit := **proc**(D, *B*) (4.20.1)

local *k*, *l*, *r*, *a*, *b*, *n*, *L*;

L := [ ];

for *k* **from** 0 **to** *B* **do**

```
        for l from -B to B do
            r := k^2 - l^2*D;
            if r <> 0 then
                a := (k^2 + l^2*D) / r;
                b := 2*k*l / r;
                if mod(D, 4) = 1 then
                    n := a^2 - a*b - 1 / 4*b^2*(D - 1)
                else
                    n := a^2 - D*b^2
                end if;
                if n = 1 and igcd(k, l,
                r) = 1 then
                    L := [op(L), [k, l, r]]
                end if
            end if
        end do
    end do;
    L
end proc
```

```
> for d in {2,3,5} do print(findunit(d,5)) od;
```

```
[[0, -1, -2], [0, 1, -2], [1, -5, -49], [1, -4, -31], [1, -3, -17], [1, -2, -7],
    [1, -1, -1], [1, 0, 1], [1, 1, -1], [1, 2, -7], [1, 3, -17], [1, 4, -31], [1,
    5, -49], [2, -5, -46], [2, -3, -14], [2, -1, 2], [2, 1, 2], [2, 3, -14], [2,
    5, -46], [3, -5, -41], [3, -4, -23], [3, -2, 1], [3, -1, 7], [3, 1, 7], [3, 2,
    1], [3, 4, -23], [3, 5, -41], [4, -5, -34], [4, -3, -2], [4, -1, 14], [4, 1,
    14], [4, 3, -2], [4, 5, -34], [5, -4, -7], [5, -3, 7], [5, -2, 17], [5, -1,
    23], [5, 1, 23], [5, 2, 17], [5, 3, 7], [5, 4, -7]]
[[0, -1, -3], [0, 1, -3], [1, -5, -74], [1, -4, -47], [1, -3, -26], [1, -2, -11],
    [1, -1, -2], [1, 0, 1], [1, 1, -2], [1, 2, -11], [1, 3, -26], [1, 4, -47], [1,
    5, -74], [2, -5, -71], [2, -3, -23], [2, -1, 1], [2, 1, 1], [2, 3, -23], [2,
    5, -71], [3, -5, -66], [3, -4, -39], [3, -2, -3], [3, -1, 6], [3, 1, 6], [3, 2,
    -3], [3, 4, -39], [3, 5, -66], [4, -5, -59], [4, -3, -11], [4, -1, 13], [4, 1,
```

$13], [4, 3, -11], [4, 5, -59], [5, -4, -23], [5, -3, -2], [5, -2, 13], [5, -1,$
$22], [5, 1, 22], [5, 2, 13], [5, 3, -2], [5, 4, -23]]$

$$[[0, -1, -5], [0, 1, -5], [1, 0, 1]] \tag{4.20.2}$$

4.21. Lucas-Lehmer-teszt a Mersenne-számokra.

```
> #
  # This procedure do Lucas-Lehmer-test for Mersenne
  # numbers M[n]=2^n-1. The exponents are taken from
  # the list L. The result is the sequence of the
  # for which M[n] is prime.
  #
  lucaslehmer:=proc(L::list(posint)) local n,M,i,vi,nL;
  nL:=[];
  for n in L do vi:=4; M:=2^n-1;
    for i to n-2 do vi:=modp(vi&^2-2,M) od;
    if vi=0 then nL:=[op(nL),n] fi;
  od; nL end;
```

(4.21.1)

```
lucaslehmer := proc(L::(list(posint)))
  local n, M, i, vi, nL;
  nL := [];
  for n in L do
    vi := 4;
    M := 2 ^ n - 1;
    for i to n - 2 do
      vi := modp(vi &^ 2 - 2, M)
    end do;
    if vi = 0 then
      nL := [op(nL),
      n]
    end if
  end do;
  nL
end proc
```

```
> Mersenne:=[2,3,5,7,13,17,19,31,67,127,257]; lucaslehmer
  (Mersenne);
  L:=[i$i=2..257]; lucaslehmer(L);
```

$$Mersenne := [2, 3, 5, 7, 13, 17, 19, 31, 67, 127, 257]$$

$$[3, 5, 7, 13, 17, 19, 31, 127]$$

$L := [2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 255, 256, 257]$

$$[3, 5, 7, 13, 17, 19, 31, 61, 89, 107, 127] \quad (4.21.2)$$

4.22. Feladat.

4.23. Valószínűségi teszt.

```
>
```

4.24. Feladat.

```
> interface(verboseproc=2);
```

$$1 \quad (4.24.1)$$

```
> print(`isprime`);
```

proc(n) (4.24.2)

option

remember, system,

Copyright (c) 1993 Gaston Gonnet, Wissenschaftliches Rechnen, ETH Zurich. All rights reserved.;

```
local btor, nr, p, r;
if not type(n,
'integer') then
    if type(n, 'numeric') then
        error "argument must be an integer"
    else
        return 'isprime(n)'
    end if
end if;
if n < 2 then
    false
elif member(n,
`isprime/w`) then
    true
elif igcd(2305567963945518424753102147331756070,
n) <> 1 then
    false
elif n < 10201 then
    true
elif igcd(
    84969694892334181105323399091873499659260625866489\
    27366115454263422038932707693909090694773095091375\
    97869171186680288614993338250976823867229837379629\
    30667576741311267365789364407881571869698937306331\
    30664786204486249492573240226273954373636390387526\
    81667586612559568346306972204475122988482222285500\
    26837863425199602259963013159456444700647206966217\
    047724452891592786711 3, n) <> 1 then
    false
elif n < 1018081 then
    true
else
```

```
        return gmp_isprime(n)
    end if
end proc
```

▶ 4.25. Megjegyzés.

▶ 4.26. Williams p+1 módszere.

▶ 4.27. Lemma.

▼ 4.28. Feladat.

```
> #
  # This procedure is Williams' p+1 method for factorization of
  n.
  # P is the parameter for the Lucas sequence. Calculation of
  V's
  # goes up to V_k!.  The result is the factor found;
  # gcd is calculated after m steps.
  #

  williams:=proc(n::posint,P::integer,k::posint,m::posint)
  local g,x,i,j; x:=P;
  for i from 2 by m to k do
    for j from i to i+m-1 while j<=k do
      x:=lucasV(j,x,1,n)[1];
    od;
    g:=igcd(x-2,n);
    if g>1 then RETURN(g) fi;
  od; igcd(x-2,n) end;
```

```
williams := proc(n::posint, P::integer, k::posint, m::posint)                (4.28.1)
    local g, x, i, j;
    x := P;
    for i from 2 by m to k do
        for j from i to i + m - 1 while j <= k do
            x := lucasV(j, x, 1, n)[1]
        end do;
        g := igcd(x - 2, n);
        if 1 < g then
            RETURN(g)
```

```
        end if
    end do;
    igcd(x − 2, n)
end proc
```

```
> williams(25852,3,10,1); williams(999863*999883*999907,3,1000,
  1);
```

$$4$$

$$999907 \qquad (4.28.2)$$

- 5. Alkalmazások
- 6. Számok és polinomok
- 7. Gyors Fourier–transzformáció
- 8. Elliptikus függvények
- 9. Számolás elliptikus görbéken
- 10. Faktorizálás elliptikus görbékkel
- 11. Prímteszt elliptikus görbékkel
- 12. Polinomfaktorizálás
- 13. A szita módszerek alapjai
- 14. Az AKS teszt